

# TWO-POST - I12

**NEW!**

*Engineered to perform... Built to last!*

Powder coat finish;  
more durable than  
conventional finishes

Padded shut-off bar to  
prevent damage caused by  
lifting a vehicle too high

Two heavy-duty  
push-type cylinders  
designed to minimize  
down-time by  
requiring little  
maintenance



Shown: Model I12  
12,000 lbs. capacity

## Engineering Excellence

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

## Product Integrity

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.



**Two-Post  
I12 is  
Gold  
Certified**

**FORWARD  
LIFT**

### I12 Series Features:

- 12,000 lbs. capacity for raising most passenger cars, trucks and vans.
- The I12 is third party certified by ALI.
- Hydraulic cylinders in each column
  - Full stroke
  - Cylinder rod concealed inside carriage
- Overhead cable equalization.
- Single point lock release
- Large rubber-padded swivel adapters with extra height extensions (4-1/2" and 8-1/2") are standard.
- Spring operated arm restraints, disengage at floor level.
- Padded overhead height limit switch bar.
- Durable powder coat finish - standard color of lift is blue with yellow arms. Red lift with yellow arms also available at no extra cost.



Shown: Model I12  
12,000 lbs. capacity

### Available Options:

- Adapter storage bracket kit
- Special truck adapters
- Air/Electric work station with air regulator and oiler



Shown: Model I12  
12,000 lbs. capacity

| Specifications                  | I12   |
|---------------------------------|---|
| Capacity                        | 12,000 lbs. (5443kg)                        |
| Rise Height                     | 82-1/2" (2095mm) with adapters              |
| Adjustable Overall Height       | 165-1/4" (4197mm), 177" High Setup (4496mm) |
| Overall Width                   | 150-3/8" (3822mm)                           |
| Drive Through                   | 109-1/2" (2781mm)                           |
| Floor to Overhead Switch        | 159-3/8" Low (4051mm), 169-1/2" High (4305) |
| Front Arm Reach                 | Min. 38-1/2" (978mm), Max. 57-1/2" (1461mm) |
| Rear Arm Reach                  | Min. 38-1/2" (978mm), Max. 57-1/2" (1461mm) |
| Lifting Pad Height              | 6" (152mm)                                  |
| Lifting Pad Height w/Short Ext. | 10-1/2" (267mm)                             |
| Lifting Pad Height w/High Ext.  | 14-1/2" (368mm)                             |
| Width Between Columns           | 123-1/4" (3131mm)                           |
| Motor                           | 2 HP  |
| Voltage                         | 208v - 230v                                 |
| Speed of Rise                   | 60 seconds                                  |

Specifications subject to change without notice or liability



Forward Lift  
996 Industrial Drive  
Madison, IN 47250

Phone: 800.423.1722  
Fax: 812.273.7329  
www.forwardlift.com

Li# Forward I12\_2009.10

©2009 Forward Lift, Forward Lift is a brand of R.L. Consolidated, A Dover Company. All rights reserved. Unless otherwise indicated, Forward Lift, R.L. Consolidated, Dover and all other trademarks are property of Dover Corporation and its affiliates.