



## **Heavy Duty Two Post Lift**

12,000 lbs. Capacity

## Features:

- 2-stage front and rear arms
- Hydraulic cylinders in each column:
  - Full stroke
- Cylinder rod concealed inside carriage
- Extended height configurations available
- Overhead cable equalization
- Spring operated arm restraints disengage at floor level
- Includes adapter extensions and storage bracket
- Single point lock release
- · Durable powder coat finish
- Five year structural, 18 month parts, and 60 day labor warranty
- ALI certified

Specifications	F12
Capacity	12,000 lbs. (5443kg)
Maximum Rise	77-1/2" (1968mm) With 5" adapter extension
Adjustable Overall Height Options	166" (4216mm) Standard Height (F12N300) 178" (4521mm) Extended Max. Height (F12N301) 154" (3912mm) (F12N302) 143" (3632mm) (F12N303)
Overall Width	140" or optional 146" (3556 / 3708mm)
Drive Through Clearance	102-3/4" or optional 108-3/4" (2609 / 2762mm)
Overhead Switch Height Options	160-1/8" (4067mm) Standard 172-1/8" (4524mm) Extended 148-1/8" (3762mm) 137-1/8" (3483mm)
Front Reach (Min./Max.)	35"/ 54" (889 / 1372mm)
Rear Reach (Min./Max.)	35"/ 54" (889 / 1372mm)
Min./Max. Adapter Height	4-3/4" (120) w/ no adapter extension 9-3/4" (248mm) w/ 5" adapter extension
Width Inside Column	120-7/8" (3070mm) Adjustable 114-7/8" (2918) Standard
Voltage/Amps	208/230, 12 amps; 208/230, 16 amps
Motor/Phase**	1ph*/2HP/50Hz; 1ph*/2HP/60Hz
Ceiling Height Required	168" (4267mm)

<sup>\*</sup>Optional 3-phase available



## Low-Profile Adapter Design:

The F12 features low-profile, oversized pads with multiple extensions to raise most vehicles on the road today. Includes four (each) adapter

extensions at 3.5" and 5"







**Engineered to perform...Built to last!** 

Phone: 800.423.1722 Fax: 812.273.7329 www.forwardlift.com





